

LARGE VOLUME WEIGHERS

Fast. Accurate. Reliable.

Filling systems for 5 lb. to 100 lb. packages!

- ◆ For food and nonfood applications
- ♦ Semi-Automatic or Fully Automatic Models

CHESTA KIGHT

Model PMB-3602 (Shown with Stainless Steel Frame and Flap Gates)



800-571-0249 www.weighrightasc.com

Model PMB-3601 **(Shown with indexing conveyor)**

PMB-3601

PMB-3602

Applications





For Filling Boxes, Bags, and Rigid Containers

- ◆ IQF Foods
- Pet Foods
- Grains/Seeds
- Nutmeats
- Candies
- Snack Foods
- Plastic Pieces
- Chemicals and more

Weights and Rates		Weights and Rates	
5 lbs.	12 cpm	5 lbs.	24 cpm
10 lbs.	10 cpm	10 lbs.	20 cpm
25 lbs.	4 cpm	25 lbs.	8 cpm
50 lbs.	2 cpm	50 lbs.	4 cpm
100 lbs.	1 cpm (2 dumps)	100 lbs.	2 cpm (2 dumps)

50% more speed! On free flowing products



PMB-3600-FL models use a gravity feed and a vibratory tray to reach weight faster than standard models.

Accuracy is 0-.02 lbs. over (depending on piece size).

MACHINE FEATURES:

- · One or two lane scale design.
- · Sanitary stainless steel contact surfaces, type 304.
- · 2 cu. ft. supply hopper (PMB-3601)
- · 4 cubic foot supply hopper (PMB-3602)
- · Programmable bulk and dribble feed settings.
- · Single or Three tray vibratory feed system.
- · Discharge spout to suit container.
- · Strain gauge load cell scale system sensitive to .02 lbs.
- · Clam type weigh bucket with 3600 cu. in. weighing capacity.
- · Air operated discharge mechanism.
- Convenient microprocessor based control panel with digital weight display (PMB-3601)
- Menu driven controls with easy-to-read graphics and help menus (PMB-3602)
- · Painted steel support frame with adjustable leveling pads.
- · Nema 4 control enclosure.
- · Footswitch or Interface cable for cycle control
- · Air filter/lubricator/regulator assembly with automatic drain.

Member of PMMI

800-571-0249

Options:

USDA Design

Stainless steel frames for washdown
Gravity Feed (for free flowing products)
Casters for portability
Supply hopper vibrator
Flap Gates for positive product cut-off
Teflon Coated contact parts
Dimpled S.S. contact surfaces
Bag Clamp for semi-automatic applications
Support frame to fit over bagger
Carton Indexing Conveyors





612-A Mills Road, Joliet, IL 60433 PH: 815-726-4626 Fax: 815-726-7638 www.weighrightasc.com

Printed in the USA